

PRO|SERIES™

HIGH PERFORMANCE FLATWORK IRONERS

F08

F08048



CHROME CYLINDER —
ELIMINATES MESSY WAX
APPLICATION & STRIPPING;
INCREASES PRODUCTIVITY

KINEMATIC™ PRESSURE
IRONING SYSTEM —
ENABLES SINGLE PASS
IRONING WITHOUT
DRYER CONDITIONING

COMPACT DESIGN
WITH RETURN-TO-FEEDER
CAPABILITY — INCREASES
PRODUCTIVITY IN A SMALL
SPACE WITH REDUCED
LABOR EXPENSE

ELECTRO-MECHANICAL
CONTROL — EASY-TO-USE

QUALITY COMPONENTS —
5/3 YEAR WARRANTY

Designed to streamline laundry operations with unique features that ensure improved flexibility, heightened production and the highest-quality finishing standards, Continental's Pro-Series™ F08 Flatwork Ironers are ideal for small-volume laundry applications. F08 Ironers—with wax-less operation—properly finish damp linens without need for costly dryer conditioning.

CONTINENTAL
GIRBAU, INC.

SPECIFICATIONS



	F08048
Cylinder Diameter inch (mm)	8.7 (220)
Usable Cylinder Length inch (mm)	47.6 (1210)
Finishing Speed ft/min (m/min)	3.5-10 (1-3)
Shipping Weight lbs (kg)	662 (300)
Net Weight lbs (kg)	540 (245)
Height inch (mm)	42.8 (1088)
Width inch (mm)	67.3 (1709)
Depth inch (mm)	30.1 (765)
Exhaust Diameter inch (mm)	3.5 (90)
Exhaust Air Flow cfm (m ³ /h)	75 (128)
Motor Power Hp (CV)	0.35 (0.35)
Circuit Protection 208-240/60/3 Amps	25
Full Load Amps	21.1/20.3
Electric Heating Kw	7.2/8

The Kinematic™ strap tensioning system ensures optimum ironing quality (top). The ironing cylinder is made of machined-steel, mirror polished and finished in chrome (middle). The electro-mechanical control (bottom) on Pro-Series™ F08 Ironers is easy-to-use.

For more detailed information on product features and benefits, please request a "Discover the Difference" brochure from your local Continental distributor, or contact Continental Girbau, Inc. at 800-256-1073. For the most current technical specifications and architectural line drawings, please visit our website at: www.cont-girbau.com.



DISTRIBUTED BY:



800-256-1073
www.cont-girbau.com
 2500 State Road 44 • Oshkosh, WI 54904
 920-231-8222 • FAX 920-231-4666