

PRO|SERIES™

HIGH PERFORMANCE FLATWORK IRONERS

F13

F13061

F13076



CHROME CYLINDER —
ELIMINATES MESSY WAX
APPLICATION & STRIPPING;
INCREASES PRODUCTIVITY

AUTOSPEED® CONTROL —
ELIMINATES TEMPERATURE
FLUCTUATIONS; ENSURES
CONSISTENT RESULTS

EXCLUSIVE MICROPROCESSOR
CONTROL — ENHANCES
EFFICIENCY & PRODUCTIVITY

QUICK CHECK™ SERVICE
PACKAGE — ALLOWS EASY
MAINTENANCE & TESTING
FROM THE CONTROL PANEL

KINEMATIC™ PRESSURE
IRONING SYSTEM — ENABLES
SINGLE PASS IRONING WITH-
OUT DRYER CONDITIONING

MAXIMUM THERMAL ISOLATION
— ERGONOMICALLY FRIENDLY

QUALITY COMPONENTS —
5/3 YEAR WARRANTY

Designed to streamline laundry operations with unique features that ensure improved flexibility, heightened production and the highest-quality finishing standards, Continental's Pro-Series™ F13 Flatwork Ironers are ideal for medium-volume laundry applications. Available in 61- and 76-inch widths and gas or electric models, F13 Ironers properly finish damp linens without need for costly dryer conditioning. The F13 features a 13-inch diameter roll and wax-less operation.

CONTINENTAL
GIABAU, INC.

SPECIFICATIONS

	F13061	F13076
Cylinder Diameter inch (mm)	12.8 (325)	12.8 (325)
Usable Cylinder Length inch (mm)	61 (1550)	76.4 (1940)
Finishing Speed ft/min (m/min)	3-16 (1-5)	3-16 (1-5)
Shipping Weight lbs (kg)	1333 (605)	1522 (690)
Net Weight lbs (kg)	992 (450)	1135 (515)
Height inch (mm)	51.9 (1319)	51.9 (1319)
Width inch (mm)	81.4 (2068)	96.7 (2456)
Depth inch (mm)	34.8 (885)	34.8 (885)
Exhaust Diameter inch (mm)	4.5 (114)	4.5 (114)
Exhaust Air Flow cfm (m ³ /h)	347 (590)	347 (590)
Motor Power Hp (CV)	0.67 (0.67)	0.67 (0.67)
Circuit Protection		
Electric 208-240/60/3 Amps	50	63
Gas 208-240/60/1 Amps	16	16
Full Load Amps	3.5	3.5
Electric Heating Kw	15.6	19.6
Gas Heating BTU/h (Kcal/h)	75600 (24000)	95500 (24090)
Gas Supply		
Natural inch wc	7 (±1)	7 (±1)
Propane inch wc	11 (±0.3)	11 (±0.3)

For more detailed information on product features and benefits, please request a "Discover the Difference" brochure from your local Continental distributor, or contact Continental Girbau, Inc. at 800-256-1073. For the most current technical specifications and architectural line drawings, please visit our website at: www.cont-girbau.com.



The Kinematic™ strap tensioning system ensures optimum ironing quality (top). The ironing cylinder is made of machined-steel, mirror polished and finished in chrome (upper-middle). Autospeed® automatically adjusts the ironing speed to assure a constant ironing temperature and even drying (lower-middle). The programmable microprocessor control (bottom) enables Pro-Series™ Ironers to be customized to match a variety of user needs.

DISTRIBUTED BY:



800-256-1073
www.cont-girbau.com
 2500 State Road 44 • Oshkosh, WI 54904
 920-231-8222 • FAX 920-231-4666