

# PRO|SERIES™

HIGH PERFORMANCE FLATWORK IRONERS

## F20

F20058

F20100

F20075

F20125



CHROME CYLINDER —  
ELIMINATES MESSY WAX  
APPLICATION & STRIPPING;  
INCREASES PRODUCTIVITY

AUTOSPEED® CONTROL —  
ELIMINATES TEMPERATURE  
FLUCTUATIONS; ENSURES  
CONSISTENT RESULTS

EXCLUSIVE MICROPROCESSOR  
CONTROL — ENHANCES  
EFFICIENCY & PRODUCTIVITY

QUICK CHECK™ SERVICE  
PACKAGE — ALLOWS EASY  
MAINTENANCE & TESTING  
FROM THE CONTROL PANEL

KINEMATIC™ PRESSURE  
IRONING SYSTEM — ENABLES  
SINGLE PASS IRONING WITH-  
OUT DRYER CONDITIONING

MAXIMUM THERMAL ISOLATION  
— ERGONOMICALLY FRIENDLY

INTEGRATED FOLDER OPTION  
— INCREASES PRODUCTION,  
QUALITY & LABOR SAVINGS

QUALITY COMPONENTS —  
5/3 YEAR WARRANTY

Continental Pro-Series™ F20 Flatwork Ironers are designed to streamline laundry operations with unique features that ensure improved flexibility, heightened production and the highest-quality finishing standards. Ideal for mid- to large-volume laundry applications, the 20-inch diameter roll ironer properly finishes damp linens without need for costly dryer conditioning. The F20 — in steam, gas or electric heat — is available in multiple finishing widths with optional integrated folding capability.

**CONTINENTAL**  
GIABAU, INC.

## SPECIFICATIONS

	GAS/ELECTRIC				STEAM	
	F20058	F20075	F20100	F20125	F20075	F20125
<b>Cylinder Diameter</b> inch (mm)	20.1 (510)	20.1 (510)	20.1 (510)	20.1 (510)	20.1 (510)	20.1 (510)
<b>Usable Cylinder Length</b> inch (mm)	58.3 (1480)	74.8 (1900)	99.6 (2530)	124.6 (3165)	74.8 (1900)	124.6 (3165)
<b>Finishing Speed</b> ft/min (m/min)	3-21 (1-6.5)	3-21 (1-6.5)	3-21 (1-6.5)	3-21 (1-6.5)	3-21 (1-6.5)	3-21 (1-6.5)
<b>Shipping Weight</b>						
without folder lbs (kg)	2447 (1110)	2976 (1350)	3571 (1620)	4001 (1815)	3538 (1605)	5269 (2390)
with folder lbs (kg)	2646 (1200)	3219 (1460)	3902 (1770)	4409 (2000)	3792 (1720)	5666 (2570)
<b>Net Weight</b>						
without folder lbs (kg)	1962 (890)	2425 (1100)	2921 (1325)	3263 (1480)	2987 (1355)	4530 (2055)
with folder lbs (kg)	2138 (970)	2634 (1195)	3197 (1450)	3616 (1640)	3197 (1450)	4883 (2215)
<b>Height</b> inch (mm)	55.9 (1420)	55.9 (1420)	55.9 (1420)	55.9 (1420)	55.9 (1420)	55.9 (1420)
<b>Width</b> inch (mm)	85.4 (2170)	102.2 (2595)	127 (3225)	152 (3860)	104.9 (2665)	154.7 (3930)
<b>Depth</b> inch (mm)	45.8 (1164)	45.8 (1164)	45.8 (1164)	45.8 (1164)	45.8 (1164)	45.8 (1164)
<b>Exhaust Diameter</b> inch (mm)	5.1 (130)	5.1 (130)	5.1 (130)	5.1 (130)	5.1 (130)	5.1 (130)
<b>Exhaust Air Flow</b> cfm (m <sup>3</sup> /h)	497 (844)	497 (844)	497 (844)	497 (844)	497 (844)	497 (844)
<b>Motor Power</b> Hp (CV)	1.48 (1.48)	1.48 (1.48)	1.48 (1.48)	1.48 (1.48)	1.48 (1.48)	1.48 (1.48)
<b>Circuit Protection</b>						
Electric 208-240/60/3 Amps	100	125	160	200	—	—
Gas 208-240/60/1 Amps	13	13	13	13	—	—
Steam 208-240/60/1 Amps	—	—	—	—	13	13
<b>Full Load</b> Amps	11.3	11.3	11.3	11.3	11.3	11.3
<b>Electric Heating</b> Kw	28	35.5	47	60	—	—
<b>Gas Heating</b> BTU/h (Kcal/h)	111000 (28000)	143000 (35500)	186500 (47000)	238000 (60000)	—	—
<b>Gas Supply</b>						
Natural inch wc	7 (±1)	7 (±1)	7 (±1)	7 (±1)	—	—
Propane inch wc	11 (±0.3)	11 (±0.3)	11 (±0.3)	11 (±0.3)	—	—
<b>Steam Heating</b> BTU/h (Kcal/h)	—	—	—	—	166500 (42000)	277750 (70000)
<b>Steam Consumption</b> lbs/h (kg/h)	—	—	—	—	146 (66)	243 (110)
<b>Steam Pressure</b> psi (bar)	—	—	—	—	116 (8)	116 (8)
<b>BHP Consumption</b> BHP	—	—	—	—	4.97	8.3



The Kinematic™ strap tensioning system ensures optimum ironing quality (top). The ironing cylinder is made of machined-steel, mirror polished and finished in chrome (upper-middle). Autospeed® automatically adjusts the ironing speed to assure a constant ironing temperature and even drying (lower-middle). The programmable microprocessor control (bottom) enables Pro-Series™ Ironers to be customized to match a variety of user needs.



For more detailed information on product features and benefits, please request a "Discover the Difference" brochure from your local Continental distributor, or contact Continental Girbau, Inc. at 800-256-1073. For the most current technical specifications and architectural line drawings, please visit our website at: [www.cont-girbau.com](http://www.cont-girbau.com).

DISTRIBUTED BY:



800-256-1073  
[www.cont-girbau.com](http://www.cont-girbau.com)  
 2500 State Road 44 • Oshkosh, WI 54904  
 920-231-8222 • FAX 920-231-4666