

PRO|SERIES™

HIGH EXTRACTION

HIGH EFFICIENCY

HIGH PRODUCTIVITY



* Stationary model shown above. Tilt model is also available.

CAPACITY	130 lbs (59 kg)
CYLINDER DIAMETER	42.5" (1080 mm)
CYLINDER DEPTH	24.4" (621 mm)
CYLINDER VOLUME	20.1 cu ft (569 dm ³)
CRATED WEIGHT	Stat: 4575 lbs (2075 kg) Tilt: 5514 lbs (2501 kg)
NET WEIGHT	Stat: 3979 lbs (1805 kg) Tilt: 4888 lbs (2217 kg)
MACHINE HEIGHT	Stat: 74.8" (1900 mm) Tilt: 82.4" (2092 mm)
MACHINE DEPTH	Stat: 57.1" (1450 mm) Tilt: 63.5" (1614 mm)
MACHINE WIDTH	Stat: 61" (1550 mm) Tilt: 64.5" (1639 mm)
DOOR OPENING	22" (559 mm)
FLOOR TO DOOR	Stat: 35.7" (908 mm) Tilt: 43.3" (1100 mm)
WASHING SPEED	35 rpm
SPIN SPEED	60.5/400/550/700/800 rpm
G-FORCE	2.2/97/183/296/387
DRAIN DIAMETER	3" (76 mm)
WATER INLETS (2)	1" (25.4 mm)
STEAM CONNECTION	3/4" (19 mm)
COMPRESSED AIR CONNECTION (TILT ONLY)	3/8" (10 mm)
MOTOR POWER	7.3 kVA
ELECTRIC HEATING POWER (OPTIONAL)	40 kVA
SHIPPING DIMENSIONS WxDXH INCHES(MM)	66.5 x 62.6 x 85 (1690 x 1590 x 2160)

* SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

NO BOLT DOWN REQUIRED — REDUCED INSTALLATION COST & DOWN TIME

HIGH SPEED G-FORCE EXTRACTION — DRY TIME REDUCED; SIGNIFICANT UTILITY SAVINGS

G-DRIVE TECHNOLOGY — REDUCED ELECTRICAL DRAW; EASY MAINTENANCE

PM MICRO CONTROL — PEAK EFFICIENCY AND PRODUCTIVITY

NO SUMP DESIGN — DECREASED WATER CONSUMPTION

QUALITY COMPONENTS — AISI-304 STAINLESS; 5/3-YEAR WARRANTY



PROCUREMENT SPECIFICATIONS



Continental's superior frame is structurally reinforced allowing for longer machine life and high spin speed (top). Due to the suspension system (upper-middle), less than 3% of the machine vibration during extract is transmitted to the floor. Therefore, no bolt down is required. The H2130 is available in Stationary model (shown on front) and Tilt model (pictured above). All Pro-Series™ washer-extractors are equipped with the PM microprocessor (bottom), Continental's most advanced control.

*Specifications are subject to change without notice. For the most current technical specifications, architectural line drawings and chemical connection information, please visit our website at www.cont-girbau.com.

DRYWEIGHT CAPACITY: Shall be a minimum of 130 lbs./cycle

CYLINDER VOL./DOOR DIAMETER: Shall be a minimum of 20.1 cu/ft. and door opening of at least 22-inches in diameter.

CABINET/CYLINDER MATERIAL: Shall be AISI Type 304 (Top/Front/Sides) and inner/outer cylinder.

PROGRAMMABLE EXTRACTION: High extract shall be a minimum of 387 G-Force with the ability to program any one of 5-extract speeds and "0" rotation at any time during the cycle.

TILT SYSTEM (Option): Unit shall provide an air operated two-way tilt system controlled from an integrated activation system mounted on the unit. The forward/back tilt should also allow the cylinder to rotate in a forward and reverse action to assist in loading and unloading. "Two hand" activation of the function is required. Also requires 101 PSI compressed air.

CYCLE SELECTION: Unit shall provide a minimum of 79 laundry cycles with a minimum of 59 cycles that may be customized to adapt to specific linen processing requirements.

PROGRAMMABLE CONTROLS: Unit shall be equipped with a microprocessor control allowing adjustment of wash/rinse temperatures, water level up to a minimum of six (6) levels, three (3) pre-programmed rotation options plus "0" rotation and the ability to program any on/off rotation combination. The control shall also allow programming of up to twelve (12) minutes per phase, delay start control, display cycle progress through LED indicator located on control panel and shall allow management to limit operator programming through the

DISTRIBUTED BY

use of a program access key and cycle lockout function.

WATER TEMPERATURE CONTROL/ PROGRESSIVE COOL DOWN:

Unit shall permit operator to pre-set wash temperatures from 33°–194°F to adapt to specific linen treatment specifications and/or government sanitary regulations. Water inlet valve shall be thermostatically controlled. Steam or Electric auxiliary heat units shall be available to field retrofit at the user option at anytime. Unit shall be capable of a gradual reduction of water temperature from wash to rinse so to reduce fabric shock/wrinkles. Reduction shall be limited to no more than 7°F per minute from 194° to 130° F.

NOISE & IN-LINE FILTERS: Unit shall produce no more than 70 dB (Measured Equivalent Continuous) at the work station of the unit. The unit shall also have standard in-line circuit filters that reduce induced noise and radiating noise for output wiring. The unit shall also provide a standard in-line DC reactor for improving the input power-factor and reducing harmonics when the voltage imbalance exceeds 2%.

WATER RE-USE SYSTEM (Option):

Unit shall provide all control function and ability to allow a field added water reclamation system capable of reclaiming rinse water for use in subsequent wash, pre-wash and initial rinse phases.

AUTOMATIC CHEMICAL INJECTION CHEMICAL DISPENSER:

Unit shall provide five (5) independent chemical injection connections for automatic dispensing of liquid chemicals with a minimum of five (5) independent activation signals. For safety purposes all connection

ports shall be mounted on the rear of the machine. Unit shall be equipped with a side mounted dispenser containing five (5) independently controlled dispensing compartments.

PROGRAM ACCELERATOR/ VISUAL CYCLE INDICATOR:

Unit shall allow operator to manually accelerate program to permit bypass of any program step. Accelerator control and visual cycle indicator shall be conveniently located on the microprocessor control and shall allow operator to monitor cycle progress/position.

BEARING HOUSING: Shall be of solid one (1) piece construction for optimum structural support.

SUSPENSION SYSTEM:

Unit shall be equipped with an internal suspension system capable of absorbing up to 95% of transmitted load dynamic energy (vibration) and isolating it away from electrical components, major mechanical components (bearings, shaft, frame) and the floor. Unit shall be freestanding and not require bolt down or pin attachment to floor structure and should require no additional foundation from standard commercial construction for mounting. Dynamic load to floor shall not exceed 661 pounds with a frequency of 13.5 Hz.

VOLTAGE/AMP REQUIREMENT:

208-240/60/3 standard voltage with no more than 30-amp service requirement (15-amp@440-480)

MACHINE WARRANTY:

Limited Warranty—3 Years on all machine parts. 5 Years—Mainframe, inner cylinder, including shaft coupler, bearings and seals.

APPROVALS/CERTIFICATION:

A minimum of CSA or ETL, ISO 9001 & 14001 Quality and Environmental Impact Standards.

